Steven M. Hoffberg

```
From: Steven M. Hoffberg [steve@hoffberg.org]
         Thursday, November 18, 2004 12:18 PM
 Sent:
 To:
         'Nguyen, Nga'
 Subject: 09/599,163 token.c
/* -----
* TVS Token handling
* Copyright (c) 1995 Newshare Corporation
*/
#define TOKEN IMPLEMENTATION
                                                 /* leave this at the top */
#include <stdio.h>
#include <stdlib.h>
#include <strings.h>
#include <unistd.h>
#include <errno.h>
#include <ctype.h>
#include <time.h>
#include <sys/types.h>
#include <netinet/in.h>
                                        /* to swap byte order */
#include "tvs util.h"
                                   /* some tvs externals */
extern int tvs sizeof profile();
/* token "flags" data structure
* (future use -- currently just a "magic" data structure)
struct token flags {
  unsigned int version: 4;
  unsigned int unused: 14;
  unsigned int never: 14;
};
typedef struct token_flags *TOKEN_FLAGS;
union tf bytes {
  struct token flags tfs;
  char tfc[sizeof(struct token flags)];
};
/* token data structure */
struct user token {
```

```
unsigned short
                 token version;
  unsigned short
                 server id;
                           /* DAMAGE CONTROL !!!!!!!!!!! */
  unsigned int
                profile[6];
  struct token flags t flags;
  time t
              st time;
};
typedef struct user token *TVS TOKEN;
union tk bytes {
  struct user token toks;
  char tokc[sizeof(struct user token)];
};
* I have to include this AFTER my internal definitions, not before!!!
#include "token.h"
#define PUBLIC
#define PRIVATE static
#define TVS TOKEN_VERSION 1
#define TOKEN FLAG VERSION 1
#define MALLOC(x) malloc(x)
 generate a new token data structure
* ______
PRIVATE TVS TOKEN
tvss new token()
 TVS TOKEN new;
 new = (TVS TOKEN) malloc(sizeof(struct user token));
 if (!new) return (TVS TOKEN) NULL;
 memset((char *)new, 0, sizeof(struct user token));
 new->token version = TVS TOKEN VERSION;
 return new;
}
  _____
 create a new (unencoded) token-flags data structure
```

```
*/
#define TOKEN MAGIC NEVER 0x1555
#define TOKEN MAGIC UNUSED 0x2aaa
PUBLIC TOKEN FLAGS
tvss new flags()
 TOKEN FLAGS new;
 new = (TOKEN FLAGS) malloc(sizeof(struct token flags));
 if (!new) return (TOKEN FLAGS) NULL;
 memset((char *)new, 0, sizeof(struct token_flags));
 new->version = TOKEN_FLAG_VERSION;
 new->never = TOKEN MAGIC NEVER;
 new->unused = TOKEN MAGIC UNUSED;
 return new;
}
 create AND FILL a new (unencoded) token data structure
PUBLIC TVS TOKEN
tvss make token(unsigned short s_id, TVS_PROFILE prof, TOKEN_FLAGS flags)
 TVS TOKEN new;
 new = tvss_new_token();
 tvss set profile(new, prof);
 tvss set server id(new, s id);
 tvss set flags(new, flags);
 tvss set sttime(new);
 return new;
/* ------
* insert the user profile
* ______
PUBLIC void
tvss set profile(TVS TOKEN token, TVS PROFILE prof)
{
 memcpy(token->profile, prof, tvs sizeof profile());
```

```
}
* retrieve the token's user profile
PUBLIC int
tvss_get_profile(TVS_TOKEN token, TVS_PROFILE prof)
 memcpy(prof, token->profile, tvs_sizeof_profile());
 return 1;
* set the token's server id
PUBLIC void
tvss_set_server_id(TVS_TOKEN token, unsigned short sid)
 token->server_id = sid;
 get the token's server id
PUBLIC unsigned short
tvss_get_server_id(TVS_TOKEN token)
 return token->server_id;
 _____
 * set the token's start time
PUBLIC void
tvss_set_sttime(TVS_TOKEN token)
 token->st_time = htonl((long) time((time_t) NULL));
  -----
 get the token's start time
```

```
*/
PUBLIC time_t
tvss get sttime(TVS TOKEN token)
 return ntohl(token->st time);
/* _____
* insert the token flags
* _____
PUBLIC void
tvss_set_flags(TVS_TOKEN token, TOKEN_FLAGS flags)
 memcpy((char *)&(token->t flags), flags, sizeof(struct token flags));
/* -----
* retrieve the token's user profile
*/
PUBLIC int
tvss get flags(TVS TOKEN token, TOKEN FLAGS flags)
 memcpy(flags, (char *)&(token->t flags), sizeof(struct token flags));
 return 1;
* tvss_token_fmt_is_valid - make sure we dont receive just barf!
* ______
PUBLIC int
tvss token fmt is valid(TVS TOKEN token)
 if (token->token_version != TVS_TOKEN_VERSION) return 0;
 if (token->t flags.version != TOKEN FLAG VERSION) return 0;
 if (token->t flags.unused != TOKEN MAGIC UNUSED) return 0;
 if (token->t flags.never != TOKEN MAGIC NEVER) return 0;
 return 1;
       _____
 encode it
```

```
*/
#define MAX TOKEN LENGTH 128
PUBLIC char *
tvss encode token(TVS TOKEN token)
 char *string;
 int len = MAX_TOKEN_LENGTH;
 string = (char *) MALLOC(len);
 if (!string) return (char *) NULL;
 if (!tvs_encode((char *) token, sizeof(struct user_token), string, &len))
  return (char *) NULL;
 string[len] = '\0';
 return (char *)string;
* decode it
PUBLIC TVS TOKEN
tvss decode token(char *string)
{
 int len:
 TVS TOKEN token;
 len = sizeof(struct user token);
 token = tvss_new_token();
 if (!tvs_decode(string, (char *) token, &len))
  return (TVS TOKEN) NULL;
 return token;
}
Very truly yours,
Steven M. Hoffberg
Milde & Hoffberg, LLP
Suite 460
10 Bank Street
White Plains, NY 10606
(914) 949-3100 tel.
(914) 949-3416 fax
steve@holfberg.org
www.hoffberg.org
```

Confidentiality Notice: This message, and any attachments thereto, may contain confidential information which is

legally privileged. The information is intended only for the use of the intended recipient, generally the individual or entity named above. If you believe you are not the intended recipient, or in the event that this document is received in error, or misdirected, you are requested to immediately inform the sender by reply e-mail at Steve@Hoffberg.org and destroy all copies of the e-mail file and attachments. You are hereby notified that any disclosure, copying, distribution or use of any information contained in this transmission other than by the intended recipient is strictly prohibited.